

Finishing Solutions For Textile

CPET Polyethylene Trolleys



TEXTILE DYEHOUSE TROLLEYS / TRANSPORTING TROLLEYS FOR RING BOBBINS

- LLPE (Low Density Linear Polyethylene) body, resistant to impacts and bending, light-weight, easily handled, completely antistatic.
- Longest lifetime compared to other materials such as fiber or PVC.
- Body thickness 6mm, rust-free, clean, joint less and smooth inner surface, provides a very clean transport of products avoiding contact to metal surfaces.
- Metal protective frame.
- Heavy-duty polyamide (white) covered with polyurethane (red) casters with protected bearings, against humidity and dust. (Essential for dye houses)
- Polyethylene Body Parts are in 3% conical shape to be inserted in each other for easy transportation.
- Plastic Body, Metal Frame and casters may be supplied separately

Technical Specifications	CPET1200	CPET1250	CPET1400	CPET1600	CPET2000	Technical Specifications	CPECT1250
Inner height	65 cm.	80 cm.	57 cm.	80 cm.	80 cm.	Inner height	90 cm.
Inner width x depth	98 x 120 cm.	100 x 125 cm.	98 x 140 cm.	100 x 160 cm.	100 x 200 cm.	Inner diameter	125 cm.
PE weight	23 Kg.	26 Kg.	28 Kg.	40 Kg.	50 Kg.	PE weight	30 Kg.
Load Capacity	800 Kg.	1000 Kg.	1100 Kg.	1250 Kg.	1600 Kg.	Load Capacity	600 Kg.

*** Concorde is a registered Trade Mark of Cihan Makina A.S. ***

www.cihanmakina.com / cihan@cihanmakina.com - www.concorde-machines.com / concorde@concorde-machines.com

Head Office: Tekstilkent Koza Plaza A Blok 25.Kat NO: 96 34235 Esenler, Istanbul, TURKEY Tel: +90-212-438 42 50 (Pbx) Fax: +90-212-438 42 40

Factory: Organize Sanayi Bolgesi, 4. Cadde No:8 26110 Eskisehir, Turkey Tel: +90-222-236 00 64 +90-222-236 13 80/ 81/82/ 83

Fax: +90-222-236 03 48 E-mail: fabrika@cihanmakina.com

*** Since 1950 ***

