

## CRCM1 - CRCM2 REGIONAL CRINKLE MACHINE

Machine for permanently creasing specific zones on woven cotton fabric.

- Ergonomically designed
- Fast and easily handled, requires only one operator
- Improves material quality

★ Pocket Area

★ Heel Area

★ Back Knee Area

★ Limited to your imagination!



### Variable Heat control

Variable heat control is a must for achieving different affects.

### Variable Duration control

Length of time is fully controllable for achieving desired creases.

### Variable Pressure control

Variable pressure can produce unlimited crease designs.

### Adjustable Crease Length control

Crease designs can be altered by adjustable crease length control.



Technical Specifications	CRCM1	CRCM2
Overall machine height	49 cm.	49 cm.
Overall machine width x depth	53 x 80 cm.	53 x 80 cm.
Overall machine weight	70 Kg.	75 Kg.
Processing Air Requirement	6 Bar	6 Bar
Crinkle Pressure	0 - 3.2 Kg/cm <sup>2</sup>	0 - 3.2 Kg/cm <sup>2</sup>
Heat Control System	P.I.D. Control	P.I.D. Control
Heat Range	0 - 240° Centigrade Degrees	0 - 240° Centigrade Degrees
Power Consumption	1 Kw	1 Kw
Electrical requirement	220V - 240V AC 50Hz	220V - 240V AC 50Hz
Production Rate	500 pcs. / 8 hrs.	500 pcs. / 8 hrs.